



CS-U9TKH-8

MODEL	(50Hz)	Indoor	CS-U9TKH-8
		Outdoor	CU-U9TKH-8
Cooling Capacity	(min-max)	kW	2.55 (0.84-3.20)
	(min-max)	Btu/h	8,700 (2,860-10,900)
CSPF			5.60
EER	(min-max)	W/W	3.75 (3.73 ~ 3.64)
Electrical Data	Voltage	V	220
	Current	A	3.4
	Power Input (mix-max)	W	680 (225-880)
Moisture Removal		L/h	1.6
		(Pt/h)	3.4
Air Circulation	Indoor	m ³ /min (ft ³ /min)	10.6 (375)
	Outdoor	m ³ /min (ft ³ /min)	26.5 (940)
Noise Level	Indoor (H / L / Q-Lo)	dB (A)	38/26/23
	Outdoor (H / L)	dB (A)	47
Dimensions	Height	mm	295 (511)
		inch	11-5/8 (20-1/8)
	Width	mm	919 (650)
		inch	36-3/16 (25-19/32)
	Depth	mm	199 (230)
		inch	7-27/32 (9-1/16)
Net Weight	Indoor	kg (lb)	9 (20)

	Outdoor	kg (lb)	20 (44)
Refrigerant Pipe Diameter	Liquid Side	mm	Ø 6.35
		inch	1/4
	Gas Side	mm	Ø 9.52
		inch	3/8
Pipe Extension	Chargeless Pipe Length	m	7.5
	Maximum Pipe Length	m	20
	Maximum Elevation Length	m	15
	Additional Refrigerant Gas* *	g/m	10
Power Supply			Indoor

Copyright © 2015 Panasonic Vietnam CSKH: 1800 1593 / (04) 3767 7360